



10.5-Inch Wide Web Printer!

M-10e



This M10e printer has been especially designed to meet the needs of a range of industries, including shipping and logistics, electronics and general manufacturing and paper and timber. The optional real time clock, cutter, dispenser and memory expansion also extend the 10.5 inch printer's versatility to meet all the needs of your individual application.

- 10.5" Wide Print Area
- 305 dpi Resolution
- Fast Processing Speed
- Heavy-Duty Casing
- 22MB Standard Memory
- Windows® Driver

The Wide Web Specialist

SATO M-10e - Specifications

Processor:

32-BIT RISC

Media:

Roll or fan-fold die cut labels

Min. 5.16" (131mm) W x 1.7" (43mm) L

Max. 10.5" (266.7mm) W x approx. 16.5" (420mm)

Max. 0.008" (0.21mm) Caliper

Max 3" (76.2mm) Inner Diameter

Max 7.8" (200mm) Roll Diameter - Wind Face-In

Bar Code Symbolologies:

Elementary: UPC-A/E, EAN-8/13, Code 39/93/128, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet, UCC/EAN 128
2-Dimensional: PDF417, Maxicode, Data Matrix, QR Code, Vericode

Bar Code:

2:1, 3:1, 5:2 ratio; programmable height up to 999 dots

Human Readable Fonts:

12 proportional, mono-spaced and outline fonts (Code table 858)
Internal CG Triumvirate® & CG Times® fonts plus downloaded TrueType® fonts

Self Diagnosis Check Features:

Head, Paper-End, Ribbon-Near-End, Ribbon End, Head Open, Memory Card Error, Test Print, Cutter Cover Open

Other Features:

Status Report, Graphics, Sequence, Form Overlay Store, Custom Design Character, Reverse Image, Line Print, Hex Dump Print, Format Store, Paper Auto Loading

Dimensions:

18.7" (475mm) x 12.3" (313.4mm) x 12.6" (319.2mm)

Weight:

50.7 lb. (23kg)

Power:

AC 100-240V, auto-switching/Peak 560VA,560W

Options:

Cutter, Dispenser, Real Time Clock, Memory Expansion, Stacker

**Printing Method**

Thermal Transfer/Direct Thermal

Print Resolution

305 dpi (12 dots/mm)

Printing Speed

Up to 5 inches per second

Print Area

Max. Width: 266mm

Max. Length: 420mm

Memory

16 MB Std. Memory RAM

6 MB Flash Memory

16 MB PCMCIA - Opt.

Plug-In Interface Modules

Optional Interfaces Modules:

- Serial - RS232 (up to 57.6k bps)
- Parallel - IEEE1284 (ECP)
- USB
- Ethernet - 10/100BaseT
- Twinax/Coax

SATO Europe makes no guarantee that the above features are available in all models, and specifications are liable to change, without notice.

SATO EUROPE GMBH · Halskestr. 15-19 · D-40880 Ratingen

Tel.: +49 (0) 21 02 / 55 66-0 · Fax: +49 (0) 21 02 / 55 66 555

Internet: www.sato-europe.com

SATO
SATO EUROPE